

**493**

## No-Skive Compact

High pressure water cleaning applications



- One wire *No-Skive* construction
- For water up to +120 °C constant temperature

### Primary Applications

High pressure water cleaners

### Construction

Inner tube: Synthetic rubber

Reinforcement: One high-tensile steel wire braid

Cover: Synthetic rubber , black or blue

Temperature Range .....Water max. +120 °C

### Fitting Series



| Part Number | Hose I.D. |      |      |      | Hose O.D.<br>mm | Pressure Rating              |      |                            |      | min. bend radius<br>mm | weight<br>kg |
|-------------|-----------|------|------|------|-----------------|------------------------------|------|----------------------------|------|------------------------|--------------|
|             | DN        | Inch | Size | mm   |                 | max. working pressure<br>MPa | psi  | min. burst pressure<br>MPa | psi  |                        |              |
| 493-4       | 6         | 1/4  | -4   | 6.4  | 13.4            | 20.0                         | 2898 | 60.0                       | 8695 | 60                     | 0.18         |
| 493-4-BLU   | 6         | 1/4  | -4   | 6.4  | 13.4            | 20.0                         | 2898 | 60.0                       | 8695 | 60                     | 0.18         |
| 493-5       | 8         | 5/16 | -5   | 7.9  | 15.0            | 20.0                         | 2898 | 60.0                       | 8695 | 75                     | 0.21         |
| 493-5-BLU   | 8         | 5/16 | -5   | 7.9  | 15.0            | 20.0                         | 2898 | 60.0                       | 8695 | 75                     | 0.21         |
| 493-6       | 10        | 3/8  | -6   | 9.5  | 17.4            | 20.0                         | 2898 | 60.0                       | 8695 | 90                     | 0.25         |
| 493-6-BLU   | 10        | 3/8  | -6   | 9.5  | 17.4            | 20.0                         | 2898 | 60.0                       | 8695 | 90                     | 0.25         |
| 493-8       | 12        | 1/2  | -8   | 12.7 | 20.6            | 17.5                         | 2536 | 52.5                       | 7608 | 110                    | 0.33         |
| 493-8-BLU   | 12        | 1/2  | -8   | 12.7 | 20.6            | 17.5                         | 2536 | 52.5                       | 7608 | 110                    | 0.33         |

WKS rubber hand grip for No-Skive high pressure water cleaning hoses can be found on page Eb-20.

The combination of high temperature and high pressure could reduce the hose life.

Also available on reels under part number 493-xx-RL

Hose layline example

PARKER NO-SKIVE 493-5 WP 20,0 MPa (2898 PSI) 1" x 8 mm (5/16) max. 120°C WATER