

Nominal Diameter

5,5

 = 25 mm²


Rectus Series

22



Coupling system with single-hand operation. High Flow valve for optimum flow and low pressure drop. Specially suited to use with gaseous media in industry. The steel sleeve counters oscillating forces. The high insertion depth is guaranteed by an optimised plug guide.

Series 22 with additional end connections available on request.

Dust Protections  (P. 250)
for Coupling Part.-No. SK23S

Working Temperature*
-20°C up to +100°C (NBR)
depending on the medium.

* For temperatures below -20°C and over +100°C and depending on the medium, other seal variants (FKM, EPDM, FFKM) are available.

**Working Pressure****

35 bar

** maximum static working pressure with design factor 4 to 1.

Material

Coupling: Brass / Steel nickel plated

Plug: Steel nickel plated or Brass

Seals: NBR

Technical Description

Connecting Force 0 bar: 40 N


Connecting Force 6 bar: 120 N

Interchangeability (KA only)

- Rectus 14
- ARO 210
- Parker 50
- Cejn 300
- Orion 44510
- JWL 522 + JWL 532
- various Swiss Products

Flow diagrams




Air





Couplings – with valve




Series 22KA

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 Male Thread	R 1/4	19	61	12	23		22KAAK13MPN
	R 3/8	19	60	12	23		22KAAK17MPN
	R 1/2	22	61	17	23		22KAAK21MPN
 Female Thread	G 1/4	19	56	9	23		22KAIW13MPN
	G 3/8	19	55	9	23		22KAIW17MPN
	G 1/2	24	58	9	23		22KAIW21MPN
 Hose Barb	6 mm	19	74	25	23		22KATF06MPN
	8 mm	19	74	25	23		22KATF08MPN
	9 mm	19	74	25	23		22KATF09MPN
	10 mm	19	74	25	23		22KATF10MPN
	13 mm	19	74	25	23		22KATF13MPN



Plugs – without valve

Series 22SF

	Connection A	HEX mm	L mm	L1 mm	D mm	Version	Part Number
 Male Thread	R 1/8	12	35	9		Steel	22SFAK10SXN
	R 1/4	14	41	12		Steel	22SFAK13SXN
	R 1/4	14	41	12		Brass	22SFAK13MXX
	G 1/4	14	41	12		Brass	22SFAW13MXX
	R 3/8	17	41	12		Steel	22SFAK17SXN
	G 3/8	17	41	12		Brass	22SFAW17MXX
	R 1/2	22	46	17		Steel	22SFAK21SXN
	G 1/2	22	46	17		Brass	22SFAW21MXX
 Female Thread	G 1/4	17	35	9		Steel	22SFIW13SXN
	G 1/4	17	35	9		Brass	22SFIW13MXX
	G 3/8	19	35	10		Steel	22SFIW17SXN
	G 1/2	24	35	12		Steel	22SFIW21SXN
 Hose Barb	6 mm		49	25	12	Steel	22SFTF06SXN
	6 mm		49	25	12	Brass	22SFTF06MXX
	8 mm		49	25	12	Steel	22SFTF08SXN
	10 mm		49	25	12	Steel	22SFTF10SXN
	10 mm		49	25	12	Brass	22SFTF10MXX
	13 mm		49	25	15	Steel	22SFTF13SXN