


Product data sheet

Specifications



current transformer, FuPacT
ISFL250 to ISFL1250, class 1,
250/5A, 5VA

LV480886

Main

Range of product	ISFL250...630 ISFL1250
Range	FuPacT
Product or component type	Current transformer
Device application	Power supply
Range compatibility	FuPacT ISFL ISFL250 fuse-switch disconnecter FuPacT ISFL ISFL400 FuPacT ISFL ISFL630 FuPacT ISFL ISFL1250
Current transformer ratio	250/5 A
Power consumption in VA	5 VA

Complementary

Accessory / separate part category	Measurement accessory
Current transformer type	Measurement class 1
Maximum safety factor	5
[Ue] rated operational voltage	800 V AC 50/60 Hz
IP degree of protection	IP20
Standards	IEC 60044-1 VDE 0414 BS 7626
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...80 °C
Height	78 mm
Width	60 mm
Depth	30 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	184 g

Package 1 Height	4.5 cm
Package 1 width	6.3 cm
Package 1 Length	8 cm
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Weight	4.135 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------